

NAME

`ares_process` – Process events for name resolution

SYNOPSIS

```
#include <ares.h>
```

```
void ares_process(ares_channel channel, fd_set *read_fds,
fd_set *write_fds)
```

```
void ares_process_fd(ares_channel channel, ares_socket_t read_fd, ares_socket_t write_fd)
```

DESCRIPTION

The **ares_process(3)** function handles input/output events and timeouts associated with queries pending on the name service channel identified by *channel*. The file descriptor sets pointed to by *read_fds* and *write_fds* should have file descriptors set in them according to whether the file descriptors specified by *ares_fds(3)* are ready for reading and writing. (The easiest way to determine this information is to invoke **select** with a timeout no greater than the timeout given by *ares_timeout(3)*).

The **ares_process** function will invoke callbacks for pending queries if they complete successfully or fail.

ares_process_fd(3) works the same way but acts and operates only on the specific file descriptors (sockets) you pass in to the function. Use **ARES_SOCKET_BAD** for "no action". This function is of course provided to allow users of c-ares to void **select()** in their applications and within c-ares.

EXAMPLE

The following code fragment waits for all pending queries on a channel to complete:

```
int nfd, count;
fd_set readers, writers;
struct timeval tv, *tvp;

while (1)
{
    FD_ZERO(&readers);
    FD_ZERO(&writers);
    nfd = ares_fds(channel, &readers, &writers);
    if (nfd == 0)
        break;
    tvp = ares_timeout(channel, NULL, &tv);
    count = select(nfd, &readers, &writers, NULL, tvp);
    ares_process(channel, &readers, &writers);
}
```

SEE ALSO

ares_fds(3), **ares_timeout(3)**

AUTHOR

Greg Hudson, MIT Information Systems
Copyright 1998 by the Massachusetts Institute of Technology.