

EPYC™ System Management Interface (E-SMI) In-band Library

Release v3.0

Generated by Doxygen 1.9.1

1 EPYC™ System Management Interface (E-SMI) In-band Library	1
1.1 Changes Notes	1
1.1.1 Highlights of release v5.2	1
1.1.2 Highlights of release v5.0	2
1.1.3 Highlights of release v4.3	2
1.1.4 Highlights of release v4.2	2
1.1.5 Highlights of release v4.1.2	2
1.1.6 Highlights of release v4.1.1	2
1.1.7 Highlights of release v4.0.0	3
1.1.8 Highlights of release v3.0.0	3
1.1.9 Highlights of minor release v2.1	3
1.1.10 Highlights of release v2.0	3
1.1.11 Highlights of release v1.5	3
1.1.12 Highlights of minor release v1.2	3
1.1.13 Highlights of minor release v1.1	4
1.1.14 Highlights of major release v1.0	4
1.2 Specifications	4
1.2.1 Processors:	4
1.2.2 Operating Systems	4
1.3 Dependency	4
1.4 Resources and Technical Support	5
1.4.1 Resources	5
1.4.2 Support	5
1.4.3 Known Issues	5

1 EPYC™ System Management Interface (E-SMI) In-band Library

NEW! E-SMI library beta 5.2 is now available

The EPYC™ System Management Interface In-band Library, or E-SMI library, is a C library for Linux that provides a user space interface to monitor and control the CPU's power, energy, performance and other system management features.

1.1 Changes Notes

1.1.1 Highlights of release v5.2

- Added support for F1A M50-5F
 - Added HSMP Floor Limit Get at core
 - Added HSMP EffFloorLimit Get at core
 - Added Freq and EFFFreq Get for whole Socket Cores with `–showall` option
 - Added HSMP Floor Limit Set at core/socket

- Added MSR Floor Limit Set core/socket
- Added Get HSMP Enabled Commands
- Added SDPS Limit Get
- Added SDPS Limit Set
- Added Dimm SPD Set
- Added Dimm SPD Get Note: All the features of this release work well only with hsmp driver tag 4.0 (https://github.com/amd/amd_hsmp) and above.

1.1.2 Highlights of release v5.0

- Added support for F1A M50-5F.
- –setcorebl to provide failure summary by comparing against Fmin/Fmax.
- –showxgmibw to take linkname and bwtype in any case(upper/lower/mix).
- Add Socket Information to Print Summary.
- DIMM Power Display in Watts.
- Logger: Update Logger Header to have right delimiter between String and Numbers.
- Convert DIMM Refresh Rate to user Friendly Names. Note: All the features of this release work well only with hsmp driver tag 3.0 (https://github.com/amd/amd_hsmp) and above.

1.1.3 Highlights of release v4.3

- Adding JSON/CSV format prints for get options.
- Adding logger(CSV) support for get options.
- Adding loopcount, loopdelay, initialdelay support for continuous monitoring of data for get options.

1.1.4 Highlights of release v4.2

- amd_hsmp.h is added as part of E-smi library.
- E-smi installation path is updated.
- Bug and warnings fixed.

1.1.5 Highlights of release v4.1.2

- Bug fix release

1.1.6 Highlights of release v4.1.1

- Clang compiler is supported.
- Some of the bugs are fixed.
- tool option is added to read the HSMP driver version.

1.1.7 Highlights of release v4.0.0

- AMD Family 0x1A and model 0x00-0x1f processors are supported in this release.
- Any of the hsmp/amd_energy/msr_safe/msr driver can be used to monitor energy.

1.1.8 Highlights of release v3.0.0

- AMD MI300 processors are supported in this release.
- Library is modified to support platform specific check in each message in an organised way.
- tool options are modified to show valid input values

1.1.9 Highlights of minor release v2.1

- Library is updated to align with changes in the processor spec

1.1.10 Highlights of release v2.0

- Supports new HSMP protocol version 5 messages, defined for Family 19h Model 10h - SP5
 - New APIs are added for platform features
 - esmi_tool is update with platform specific features

1.1.11 Highlights of release v1.5

- Supports ioctl based implementation of hsmp driver with support for following new APIs
 - Set XGMI link width for 2P connected systems
 - Set LCLK dpm level for NBIO id
 - APB Disable and Enable messages

1.1.12 Highlights of minor release v1.2

- Support to compile ESMI In-band library as static
- Support for new system management features in tool and library, such as
 - Get SMU Firmware version
 - Get PROCHOT status
 - Get clocks
 - * CPU clock frequency limit
 - * Data Fabric Clock(fclk),
 - * DRAM Memory Clock(mclk) and
 - Provide maximum DDR bandwidth(theoretical) & DDR bandwidth utilization
- Add more options and improve tool's console output for readability

1.1.13 Highlights of minor release v1.1

- Support for creating RPM and DEB packages
- Auxiliary APIs to provide system topology
- An API to read all the Energy counters on the CPU at once.
- Single command to create doxygen based PDF document
- Updated e_smi_tool supporting all the above information
- Cosmetic changes to the tool

1.1.14 Highlights of major release v1.0

- Power
 - Current Power Consumed
 - Power Limit
 - Max Power Limit
- Performance
 - Boostlimit
- Energy
 - Energy Consumed
- e_smi_tool, user application supporting all the above information.

1.2 Specifications

1.2.1 Processors:

Target released for AMD EPYC™ processor Family 19h, model 0h-1Fh, 30h-3Fh, 90h-9Fh, A0h-AFh and Family 0x1A model 0h-1Fh.

1.2.2 Operating Systems

AMD ESMI In-band library is tested on following distributions

- Ubuntu 18.04, 20.04
- SUSE SLES 15 and
- RHEL 8.1

1.3 Dependency

This new e-smi release works well with `amd_hsmp` driver version 2.4. Not all features will work with version < 2.4. Setting cpu rail iso frequency policy, df c-state enabling, xGMI pstate range setting etc will only work with 2.4 version of amd_hsmp driver.

1.4 Resources and Technical Support

1.4.1 Resources

- Documentation: https://github.com/amd/esmi_ib_library/blob/master/ESMI_Manual.pdf
- Source code: https://github.com/amd/esmi_ib_library

1.4.2 Support

Thank you for using AMD ESMI In-band Library. Please use [ESMI In-band Support](#) for bug reports, support and feature requests.

1.4.3 Known Issues

- In creating package if "make install" is used previously with "sudo", need to create package with sudo permission, "sudo make package", else permission denied error is popped.

