

ConTEXt commands

TEX

ConTeXt

commands

en / english
October 30, 2001


```
\about{...}[ref]
```

... *text*

```
\adaptlayout[...,...,...][...,...=...,...]
```

... *number*
height *dimension max*
lines *number*

```
\adding[...]
```

... *small* *medium* *big*

```
\appendix[ref,...]{...}
```

... *text*

```
\arg{...}
```

... *text*

```
\at{.1.}{.2.}[ref]
```

.1. *text*

```
\atpage[ref]
```

```
\background
```

```
\blackrule[...,...=...,...]
```

...=... see \setupblackrules

```
\blackrules[...,...=...,...]
```

...=... see \setupblackrules

```
\blank[...,...,...]
```

... *n*small n*medium n*big nowhite back white disable force reset line halffline formula fixed flexible*

```
\bookmark{.1.}{.2.}
```

.1. *name*

```
\but[ref]
```

```
\button[...,...=,...]{...}[ref,...]
```

...=... see \setupbuttons
... text

```
\CAP{...}
```

... text

```
\Cap{...}
```

... text

```
\Caps{... ... ...}
```

... text

```
\chapter[ref,...]{...}
```

... text

```
\Character{...}
```

... number

```
\character{...}
```

... number

```
\Characters{...}
```

... number

```
\characters{...}
```

... number

```
\chem{.1.}{.2.}{.3.}
```

.1. text
.2. text
.3. text

```
\clip[...,...=,...]{...}
```

...=... see \setupclipping

```
\clonefield[.1.][...,2,...][.3.][...,4,...]
```

.1. *name*
.2. *name*
.3. *name*
.4. *name*

```
\color[.1.]{.2.}
```

.1. *text*

```
\column
```

```
\comment[.1.][...,..=...]{.2.}
```

.1. *name*
..=... see \setupcomment

```
\comparecolorgroup[...]
```

... *name*

```
\comparepalet[...]
```

... *name*

```
\completecombinedlist[...][...,..=...]
```

... *name*
..=... see \setupcombinedlist

```
\completelistoffloats
```

```
\completelistofsorts
```

```
\completelistofsynonyms
```

```
\completeregister[...,..=...]
```

..=... see \setupregister

```
\convertnumber{.1.}{.2.}
```

.1. *name*
.2. *number*

```
\copyfield[.1.][...,2,...]
```

.1. *name*
.2. *name*

```
\correctwhitespace{...}
```

```
\coupleddocument[.1.][.2.][.3.]
```

.1. *name*
.2. *file*
.3. *name*
.4. *text*

```
\coupledregister[.1.]{.2.}
```

.1. *text*
.2. *text*

```
\couplemarking[.1.][.2.]
```

.1. *name*
.2. *name*

```
\couplepage[...,...,...][...,...=...,...]
```

... *name*
option *doublesided*
before *command*
after *command*

```
\couplepaper[...]
```

... *name*

```
\couplerregister[...]
```

... *name*

```
\crlf
```

```
\currentdate[...,...,...]
```

... day month weekday year dd mm jj yy d m j y referral

```
\currentheadnumber
```

```
\date[...,...=,...][...,...,...]
```

d *number*
m *number*
y *number*
... see \currentdate

```
\decouplemarking[...]
```

... *name*

```
\define[.1.]\command{.2.}
```

.1. *number*

```
\defineblank[.1.][.2.]
```

.1. *name*
.2. see \setupblank

```
\defineblock[...]
```

... *name*

```
\definebodyfont[...,.1.,...][.2.][...,...=,...]
```

.1. 5pt ... 12pt default
.2. rm ss tt mm hw cg
tf *file*
bf *file*
sl *file*
it *file*
bs *file*
bi *file*
sc *file*
ex *file*
mi *file*
sy *file*
ma *file*
mb *file*
mc *file*

```
\definebodyfontenvironment[...][...,...=,...]
```

... 5pt ... 12pt default
text *dimension*
script *dimension*
scriptscript *dimension*
x *dimension*
xx *dimension*
small *dimension*
big *dimension*

```
\definebuffer[...]
```

... *name*

```
\definecolor[...][..., ...=..., ...]
```

. . . *name*
r *text*
g *text*
b *text*
c *text*
m *text*
y *text*
k *text*
s *text*

```
\definecolorgroup[.1.][.2.][x:y:z=,...]
```

.1. *name*
.2. rgb cmyk gray s

```
\definecombinedlist[.1.][..., .2., ...][..., ...=..., ...]
```

.1. *name*
.2. *list*
. . . see \setupcombinedlist

```
\defineconversion[.1.][.2.]
```

.1. *name*
.2. *command text*

```
\definedescription[...][..., ...=..., ...]
```

. . . *name*
. . . see \setupdescriptions

```
\defineenumeration[..., .1., ...][.2.][..., ...=..., ...]
```

.1. *name*
.2. *name*
. . . see \setupenumerations

```
\definefield[.1.][.2.][.3.][..., .4., ...][.5.]
```

.1. *name*
.2. *name*
.3. *name*
.4. *name*
.5. *name*

```
\definefieldstack[.1.][..., .2., ...][..., ...=..., ...]
```

.1. *name*
.2. *name*
. . . see \setupfields

```
\definefiguresymbol[.1.][.2.][..., ...=..., ...]
```

- .1. *name*
- .2. *text*
- ...=... see \externalfigure

```
\definefloat[.1.][.2.]
```

- .1. *name*
- .2. *plural name*

```
\definefont[.1.][.2.]
```

- .1. *name*
- .2. *file*

```
\defineframed[...][..., ...=..., ...]
```

- ... *name*
- ...=... see \setupframedtexts

```
\defineframedtext[...][..., ...=..., ...]
```

- ... *name*
- ...=... see \setupframedtexts

```
\definehead[.1.][.2.]
```

- .1. *name*
- .2. *section*

```
\defineindenting[...][..., ...=..., ...]
```

- ... *name*
- ...=... see \setupindentations

```
\defineinteractionmenu[.1.][.2.][..., ...=..., ...]
```

- .1. *left right top bottom name*
- .2. *left right top bottom name*
- ...=... see \setupinteractionmenu

```
\definelabel[...][..., ...=..., ...]
```

- ... *name*
- text *text*
- location *inmargin intext*
- way *bytext bysection bychapter*
- blockway *yes no*
- headstyle *normal bold slanted boldslanted type cap small... command*
- headcolor *name*
- before *command*
- after *command*

```
\definelist[.1.][.2.][..., ...=..., ...]
```

.1. *name*
.2. *name*
...=... see \setuplist

```
\defineLogo[.1.][.2.][.3.][..., ...=..., ...]
```

.1. *name*
.2. top header footer bottom
.3. none page leftedge leftmargin left middle right rightmargin rightedge
command *command text*
state start stop

```
\defineMakeup[...][..., ...=..., ...]
```

... *name*
...=... see \setupmakeup

```
\defineMarking[.1.][.2.]
```

.1. *name*
.2. *name*

```
\defineOutput[.1.][..., .2., ...]
```

.1. *name*
.2. *name*

```
\defineOverlay[..., .1., ...][.2.]
```

.1. *name*
.2. *command*

```
\definePalet[...][..., ...=..., ...]
```

... *name*
name *name*

```
\definePaperSize[...][..., ...=..., ...]
```

... *name*
width *dimension*
height *dimension*
offset *dimension*
scale *number*

```
\defineparagraphs[...][..., . . . = . . . ]  
...      name  
n       number  
rule    on off  
height   fit dimension  
before   command  
after    command  
inner    command  
distance dimension  
tolerance verystrict strict tolerant verytolerant stretch  
align    left right middle
```

```
\defineprofile[...,.1.,...][...,.2.,...]  
.1.    name  
.2.    name
```

```
\defineprogram[.1.][.2.][.3.]  
.1.    name  
.2.    text  
.3.    text
```

```
\definerawfont[.1.][.2.][..., . . . = . . . ]  
.1.    name  
.2.    file  
. . . = . . . see \setupinterlinespace
```

```
\definereference[...][ref, ...]  
...      name
```

```
\definereferenceformat[...][..., . . . = . . . ]  
...      name  
left   text  
right  text  
text   text  
label  name
```

```
\definerefencelist[...][..., . . . = . . . ]  
...      name  
. . . = . . . see \setupreferencelist
```

```
\defineregister[.1.][.2.]  
.1.  
.2.    plural name
```

```
\definerule[...][..., . . . = . . . ]  
...      name  
. . . = . . . see \setuprule
```

```
\definesection[...]
```

... *name*

```
\definesectionblock[...][..., . . . = . . .]
```

... *name*
... = ... see \setupsectionblock

```
\definesorting[.1.][.2.][.3.]
```

.1.
.2. *plural name*
.3. *command*

```
\definesstartstop[...][..., . . . = . . .]
```

before *command*
after *command*
style normal bold slanted boldslanted type cap small... *command*
commands *command*

```
\definesubfield[.1.][.2.][..., .3., ...]
```

.1. *name*
.2. *name*
.3. *name*

```
\definesymbol[.1.][.2.]
```

.1. *name*
.2. *text*

```
\definesynonyms[.1.][.2.][.3.][.4.]
```

.1.
.2. *plural name*
.3. *command*
.4. *command*

```
\definetabletemplate[.1.][.2.][.3.][.4.]
```

.1. *name*
.2. *text*
.3. *text*
.4. *text*

```
\definetabulate[.1.][.2.][.3.]
```

.1. *name*
.2. *name*
.3. *text*

```
\definetext[.1.][.2.][.3.][.4.][.5.]
```

.1. *name*
.2. header footer
.3. *text*
.4. *text*
.5. *text*

```
\definetextposition[...][..., . . = . . .]
```

... *name*
. . = . . see \setuppositioning

```
\definetextvariable[.1.][.2.][..., . . = . . .]
```

. . = . . see \setuptextvariable

```
\definetype[...][..., . . = . . .]
```

... *name*
. . = . . see \setuptype

```
\definotyping[...][..., . . = . . .]
```

... file typing *name*
. . = . . see \setuptyping

```
\defineversion[.1.][..., .2. . .]
```

.1. *name*
.2. *number*

```
\description{.1.}.2.\par
```

.1. *text*
.2. *text*

```
\determineheadnumber[...]
```

... *section*

```
\determinelistcharacteristics[..., . . . . .][..., . . = . . .]
```

... *name*
. . = . . see \setuplist

```
\disableinteractionmenu[...][ref, . .]
```

... left right top bottom *name*

```
\domicile{...}
```

... *text*

\donttest

\enumeration... \par

... *text*

\externalfigure[...] [...] = ...]

... *file*

... = ... see \useexternalfigure

\field[...]

... *name*

\fieldstack[.1.] [...] [...] = ...]

.1. *name*

.2. *name*

... = ... see \setupfields

\fillinfield[.1.]{.2.}

.1. *text*

.2. *text*

\fillinline[...,...=...,...]... \par

... = ... see \setupfillinlines

\fillinrules[...,...=...,...]{.1.}{.2.}

... = ... see \setupfillinrules

\fillintext[...,...=...,...]{.1.}{.2.} \par

... = ... see \setupfillinrules

\fitfield[...]

... *name*

\fixedspaces

\followprofile{.1.}{.2.}

.1. *text*

.2. *name*

```
\followprofileversion{.1.}{.2.}{.3.}
```

.1. *text*
.2. *name*
.3. *name*

```
\followversion{.1.}{.2.}
```

.1. *text*
.2. *name*

```
\footnote[ref]{...}
```

... *text*

```
\footnotetext[ref]{...}
```

... *text*

```
\fraction{.1.}{.2.}
```

.1. *text*
.2. *text*

```
\framed[...,...=...,...]{...}
```

...=... see \setupframed
... *text*

```
\framedtext[...,...=...,...]
```

...=... see \setupframedtexts

```
\from[ref]
```

... *text*

```
\getbuffer[...]
```

... *name*

```
\getmarking[.1.][.2.]
```

.1. *name*
.2. first last previous both all current

```
\godown[...]
```

... *dimension*

```
\goto{.1.}{.2.}[ref,...]
```

.1. *text*

```
\gotobox[...][ref,...]
```

... *text*

```
\graycolor[...]
```

... *text*

```
\grid[...,...=...,...]
```

x *number*
y *number*
nx *number*
ny *number*
dx *number*
dy *number*
xstep *number*
ystep *number*
offset yes no
factor *number*
scale *number*
unit cm pt em mm ex es in
location left middle

```
\hairline
```

```
\head[ref,...]
```

```
\headnumber[...]
```

... *section*

```
\headtext{...}
```

... *text*

```
\hideblocks[...,.1,...][...,2,...]
```

.1. *name*
.2. *name*

```
\high{...}
```

... *text*

```
\h1[...]
```

... *number*

```
\in{.1.}{.2.}[ref]
```

.1. *text*

```
\indentation...\par
```

... *text*

```
\indenting[...,...,...]
```

... never not no yes always first next

```
\inframed[...,...=...]{...}
```

.1. see \setupframed

... *text*

```
\inleft[.1.][ref]{.2.}
```

.1. + - low

.2. *text*

```
\inline[ref]
```

```
\inmargin[.1.][ref]{.2.}
```

.1. + - low

.2. *text*

```
\inothermargin[.1.][ref]{.2.}
```

.1. + - low

.2. *text*

```
\inright[.1.][ref]{.2.}
```

.1. + - low

.2. *text*

```
\installlanguage[...][...,...=...,...]
```

...	<i>name</i>
spacing	<u>packed</u> <u>broad</u>
lefthyphenmin	<i>dimension</i>
righthphenmin	<i>dimension</i>
state	<u>start</u> <u>stop</u>
leftsentence	<i>command</i>
rightsentence	<i>command</i>
leftsubsentence	<i>command</i>
rightsubsentence	<i>command</i>
leftquote	<i>command</i>
rightquote	<i>command</i>
leftquotation	<i>command</i>
rightquotation	<i>command</i>
default	<i>name</i>

```
\interactionbar[...,...=...,...]
```

...=... see \setupinteractionbar

```
\interactionbuttons[...,...=...,...][...,...,...]
```

...=... see \setupinteractionbar
... name

```
\item[ref,...]
```

```
\items[...,...=...,...]{...,...,...}
```

...=... see \setupitems

```
\its[ref,...]
```

```
\kap{...}
```

... text

```
\keepblocks[...,.1,...][...,.2,...]
```

.1. name
.2. all name

```
\labeling[ref]
```

```
\labels[...]
```

... name

```
\labeltext{...}
```

... text

```
\language[...]
```

... nl fr en uk de es cz ...

```
\leftaligned{...}
```

... text

```
\letters[...]
```

... name

```
\loadsorts
```

```
\loadsynonyms
```

```
\logfields
```

```
\lohi{.1.}{.2.}{.3.}
```

.1. *low*
.2. *text*
.3. *text*

```
\low{...}
```

... *text*

```
\mainlanguage{...}
```

... nl fr en uk de es cz ..

```
\mar[ref,...]{...}
```

```
\marginrule{.1.}{.2.}
```

.1. *number*

```
\margintext{.1.}[ref]{.2.}
```

.1. + - *low*
.2. *text*

```
\marking{.1.}{.2.}
```

.1. *name*
.2. *text*

```
\marking(.1.,.2.)(.3.,.4.)[.5.]
```

.1. *number*
.2. *number*
.3. *number*
.4. *number*
.5. *text*

```
\markversion
```

```
\mathematics{...}
```

... *formula*

```
\mediaeval{...}
```

... *number*

```
\menubutton[.1.][..., ...=..., ...]{.2.}[ref,...]
```

...=... see \setupframed
.1. *text*

```
\midaligned{...}
```

... *text*

```
\mirror{...}
```

```
\month{...}
```

... *number*

```
\MONTH{...}
```

... *number*

```
\moveongrid{...}
```

... top both bottom

```
\name{...}
```

... *name*

```
\nextsection
```

```
\nocap{...}
```

... *text*

```
\noheaderandfooterlines
```

```
\noindenting
```

```
\nolist{...}
```

... *text*

```
\nomarking{...}
```

... *text*

```
\nomoreblocks
```

```
\nomorefiles
```

```
\nop
```

```
\nospace
```

```
\note[ref]
```

```
\notopandbottomlines
```

```
\nowhitespace
```

```
\numbers{...}
```

... *number*

```
\overbar{...}
```

... *text*

```
\overbars{... ... ...}
```

... *text*

```
\overstrike{...}
```

... *text*

```
\overstrikes{... ... ...}
```

... *text*

\packed

\page[...,...,...]

... yes makeup no preference bigpreference left right disable last quadruple even odd blank empty reset

\pagerefERENCE[*ref*]

\pageTYPE[...]

... *name*

\paragraph

\part[*ref*,...]{...}

... *text*

\periodS[...]

... *number*

\placebookmarks[...,.1,...][...,.2,...]

.1. *name*

\placecombinedlist[...][...,..=...,...]

... *name*

..=.. see \setupcombinedlist

\placefloat[.1.][*ref*,...]{.2.}{.3.}

.1. left right here top bottom inleft inright inmargin margin page opposite always force tall

.2. *text*

.3. *text*

\placefootnotes[...,...=...,...]

..=.. see \setupfootnotes

\placeformula[*ref*,...]{.1.}\$\$.2. \$\$

.1. *text*

.2. *formula*

```
\placelegend{.1.}{.2.}
```

- .1. *text*
- .2. *text*

```
\placelist[...,...,...][...,...=...,...]
```

- ... *name*
- ...=... see \setuplist

```
\placelistoffloats
```

```
\placeListOfsorts
```

```
\placeListofsynonyms
```

```
\placeLocalFootnotes[...,...=...,...]
```

- ...=... see \setupFootnotes

```
\placeLogos[...,...,...]
```

- ... *name*

```
\placeOnGrid{.1.}{.2.}
```

- .1. see \moveOnGrid

```
\placeOnTopOfEachOther{.1.}{.2.}
```

- .1. *text*
- .2. *text*

```
\placeReferenceList[...,...,...]
```

- ... *name*

```
\placeRegister[...,...=...,...]
```

- ...=... see \setupRegister

```
\placeRule[...]
```

- ... *name*

```
\placeSideBySide{.1.}{.2.}
```

- .1. *text*
- .2. *text*

```
\placesubformula[ref,...]{.1.}$$.{2.}$$
```

.1. *text*
.2. *formula*

```
\placetextvariable[...]
```

... *name*

```
\position(.1.,.2.){.3.}
```

.1. *number*
.2. *number*
.3. *text*

```
\positiontext[.1.]{.2.}
```

.1. *name*
.2. *text*

```
\processblocks[...,.1.,...][...,2,...]
```

.1. *name*
.2. *name*

```
\processpage[...,.1.,...][.2.]
```

.1. *name*
.2. yes no

```
\program[...]
```

... *name*

```
\publication[ref]
```

```
\quotation{...}
```

... *text*

```
\quote{...}
```

... *text*

```
\ran{...}
```

```
\redo[...]
```

... *n***text*

```
\ref[...][ref]
```

... *tpse*
... *text*

```
\reference[ref]{...}
```

... *text*

```
\referral[...,...=...,...]
```

bet *text*
ken *text*
dat *text*
from *text*
to *text*
ref *text*

```
\referraldate
```

```
\referring(.1.,.2.)(.3.,.4.)[.5.]
```

.1. *number*
.2. *number*
.3. *number*
.4. *number*
.5. *text*

```
\register[.1.]{...+.2.+...}
```

.1. *text*
.2. *text*

```
\remark(.1.,.2.)(.3.,.4.)[...,...=...,...]{.5.}
```

.1. *number*
.2. *number*
.3. *number*
.4. *number*
.5. *text*
...=... see \setupframed

```
\reservefloat[...,...=...,...][.1.][ref,...]{.2.}
```

height *dimension*
width *dimension*
frame *on off*
.1. *left right here top bottom inleft inright inmargin margin page opposite always force*
.2. *text*

```
\reset[...,...,...]
```

... *name*

```
\resetmarking[...]
```

... *name*

```
\rightaligned{...}
```

... *text*

```
\romannumerals{...}
```

... *number*

```
\Romannumerals{...}
```

... *number*

```
\rotate[...,...=...]{...}
```

...=... see \setuprotate

```
\scale[...,...=...]{...}
```

sx *number*
sy *number*

```
\screen
```

```
\section[ref,...]{...}
```

... *text*

```
\seeregister[.1.]{.2.}{...+.3.+...}
```

.1. *text*
.2. *text*
.3. *text*

```
\selectblocks[...,.1,...][...,.2,...][...=...]
```

.1. *name*
.2. *name*
criterium all *section*

```
\selectpaper[...,...=...]
```

family 1 2

```
\selectversion
```

```
\settextvariable[.1.][.2.]
```

.1. *name*
.2. *text*

```
\setupalign[...]
```

... width left right middle inner outer wide broad height bottom line reset hanging nohanging hyphenated
nohyphenated

```
\setuparranging[.,.,.,.,.]
```

... disable 2*16 2*8 2*4 2*2 2**2 2UP 2DOWN mirrored rotated doublesided negative 90 180 270

```
\setupbackground[.,.,.=.,.]
```

leftoffset *dimension*
rightoffset *dimension*
topoffset *dimension*
bottomoffset *dimension*
before *command*
after *command*
state start stop
..=.. see \setupframed

```
\setupbackgrounds[.1.][.,.2.,.][.,.=.,.]
```

.1. top header text footer bottom page paper leftpage rightpage
.2. leftedge leftmargin text rightmargin rightedge
state start stop repeat
..=.. see \setupframed

```
\setupblackrules[.,.,.=.,.]
```

width *dimension max*
height *dimension max*
depth *dimension max*
alternative a b
distance *dimension*
n *number*

```
\setupblank[...]
```

... normal standard line *dimension* big medium small fixed flexible

```
\setupblock[.,.,.,.][.,.=.,.]
```

... *name*
before *command*
after *command*
inner *command*
style normal bold slanted boldslanted type cap small... *command*
file *file*

```
\setupbodyfont[.,.,.,.]
```

... *name* serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt

```
\setupbodyfontenvironment[...][..., ...=..., ...]
```

... see \setupbodyfont
...=... see \setupbodyfont

```
\setupbottom[...][..., ...=..., ...]
```

... see \setupheader
...=... see \setupheader

```
\setupbottomtexts[.1.][.2.][.3.]
```

.1. text margin edge
.2. text section date mark pagenumber
.3. text section date mark pagenumber

```
\setupbuffer[...][..., ...=..., ...]
```

... name
paragraph number
before command
after command

```
\setupbuttons[..., ...=..., ...]
```

state start stop
...=... see \setupframed

```
\setupcapitals[..., ...=..., ...]
```

title yes no
sc yes no

```
\setupcaption[...][..., ...=..., ...]
```

... name
...=... see \setupcaptions

```
\setupcaptions[..., ...=..., ...]
```

location top bottom none high low middle
width fit max dimension
headstyle normal bold slanted boldslanted type cap small... command
style normal bold slanted boldslanted type cap small... command
number yes no
inbetween command
align left middle right no
conversion numbers characters Characters romannumerals Romannumerals
way bytext bysection

```
\setupclipping[...,...=...,...]
```

nx *number*
ny *number*
x *number*
y *number*
width *dimension*
height *dimension*
hoffset *dimension*
voffset *dimension*
mp *name*

```
\setupcolor[...]
```

... *name*

```
\setupcolors[...,...=...,...]
```

state start stop global local
conversion yes no always
reduction yes no
rgb yes no
cmyk yes no
mpcmyk yes no

```
\setupcolumns[...,...=...,...]
```

n *number*
ntop *number*
rule on off
height *dimension*
tolerance verystrict strict tolerant verytolerant stretch
distance *dimension*
balance yes no
align yes no text
blank fixed halfline line flexible big medium small
option background
direction left right
...=... see \setupframed

```
\setupcombinations[...,...=...,...]
```

before commando
inbetween commando
after commando
distance *dimension*
height *dimension* fit
width *dimension* fit
align no left right middle normal

```
\setupcombinedlist[...][...,...=...,...]
```

... *name*
level 1 2 3 4 *section* current
...=... see \setuplist

```
\setupcomment[...,...=...,...]

width   dimension
height  dimension
color   name
title   text
space   yes no
symbol  normal New Balloon Addition Help Paragraph Key
option   max
```

```
\setupcorrespondence[...,...,...]

...    formeel informeel rekening ls high middle low
```

```
\setupdescriptions[...,...,...][...,...=...,...]

...      name
headstyle normal bold slanted boldslanted type cap small... command
style    normal bold slanted boldslanted type cap small... command
color   name
width   fit broad dimension
distance dimension
sample  text
text    text
align   left middle right
margin  standard yes no dimension
location left right top serried inmargin inleft inright hanging
hang    fit broad number
before   command
inbetween command
after    command
indentnext yes no
```

```
\setupenumerations[...,...,...][...,...=...,...]

...      name
...=...  see \definedescription
location left right top serried inmargin inleft inright hanging
text    text
levels  number
conversion numbers characters Characters romannumerals Romannumerals
way    bytext bysection
blockway yes no
sectionnumber yes number no
separator  text
stopper    text
coupling   name
couplingway global local
number    no name
aligntitle no yes
start     number
```

```
\setupexternalfigures[...=...]

option   frame empty test
object   yes no
frames   on off
ymax    number
xmax    number
directory text
location local global default none
maxwidth dimension
maxheight dimension
```

```
\setupfield[.1.][...,2,...][...,..=...,...][...,..=....][...,..=...,...]
```

.1. *name*
.2. *label horizontal vertical frame*
...=... see \framed
...=... see \setupfields

```
\setupfields[...,1,...][.2.][...,..=...,...][...,..=....][...,..=...,...]
```

.1. *name*
.2. *reset label horizontal vertical frame*
...=...
n *number*
distance *dimension*
before *command*
after *command*
inbetween *command*
color *name*
style *normal bold slanted boldslanted type*
align *left middle right*
option *readonly required protected sorted unavailable hidden printable*
clickin *reference*
clickout *reference*
regionin *reference*
regionout *reference*
afterkey *reference*
format *reference*
validate *reference*
calculate *reference*
fieldoffset *dimension*
fieldframecolor *name*
fieldbackgroundcolor *name*

```
\setupfillinlines[...,..=....]
```

width *dimension*
margin *dimension*
distance *dimension*
before *command*
after *command*

```
\setupfillinrules[...,..=....]
```

width *fit broad dimension*
distance *dimension*
before *command*
after *command*
style *normal bold slanted boldslanted type cap small... command*
n *number*
interlinespace *small medium big*
separator *text*

```
\setupfloat[...][...,..=...,...]
```

... *name*
height *dimension*
width *dimension*
pageboundaries *list*
...=... see \setupframed

\setupfloats[...,...=...,...]

location left right middle
width fit *dimension*
before *command*
after *command*
margin *dimension*
spacebefore *n*medium n*big none*
spaceafter *n*small n*medium n*big none*
sidespacebefore *n*small n*medium n*big none*
sidespaceafter *n*small n*medium n*big none*
indentnext yes no
n_{top} *number*
n_{bottom} *number*
n_{lines} *number*
. = ... see \setupframed

\setupfloatsplitting[...,...=...,...]

conversion numbers characters Characters romannumerals Romannumerals character
lines *number*

\setupfooter[...][...,...=...,...]

... see \setupheader
. = ... see \setupheader

\setupfootertexts[.1.][.2.][.3.]

.1. text margin edge
.2. text section date mark pagenumber
.3. text section date mark pagenumber

\setupfootnotedefinition[...,...=...,...]

... = ... see \definedescription

\setupfootnotes[...,...=...,...]

conversion numbers characters Characters romannumerals Romannumerals
way bytext bysection
location page text columns high none
rule on off
before *command*
after *command*
width *dimension*
height *dimension*
bodyfont 5pt ... 12pt small big
style normal bold slanted boldslanted type cap small... *command*
distance *dimension*
columndistance *dimension*
margindistance *dimension*
n *number*
numbercommand \command#1
split tolerant strict verystrict *number*
. = ... see \framed

\setupforms[...,...=...,...]

method HTML FDF

```
\setupformulae[...,...=...,...]
```

```
location      left right
left          text
right         text
align          left middle right
strut          yes no
distance       dimension
margin         dimension standard yes no
leftmargin     dimension
rightmargin    dimension
indentnext     yes no
alternative    name default
spacebefore    dimension
after          dimension
```

```
\setupframed[...,...=...,...]
```

```
height         fit broad dimension
width          fit broad dimension
offset         none overlay default dimension
location       low depth
option          none empty
strut          yes no
align          no left right middle normal high low lohi
bottom         command
top            command
frame          on off overlay
topframe       on off
bottomframe    on off
leftframe      on off
rightframe     on off
frameoffset    dimension
framedepth     dimension
framecorner    round rectangular
frameradius    dimension
framecolor     name
background      screen color none foreground name
backgroundscreen number
backgroundcolor name
backgroundoffset frame dimension
backgrounddepth dimension
backgroundcorner round rectangular
backgroundradius dimension
depth           dimension
corner          round rectangular
radius          dimension
empty           yes no
foregroundcolor name
...             text
```

```
\setupframedtexts[...,...=...,...]
```

```
bodyfont       5pt ... 12pt small big
style          normal bold slanted boldslanted type small... command
left           command
right          command
before         command
after          command
inner          command
linecorrection on off
depthcorrection on off
margin         standard yes no
...=...         see \setupframed
```

```
\setuphead[...][...,...=...,...]

...
      section
style      normal bold slanted boldslanted type cap small... command
textstyle   normal bold slanted boldslanted type cap small... command
numberstyle normal bold slanted boldslanted type cap small... command
number     yes no
ownnumber  yes no
page       left right yes
continue   yes no
header     none empty high nomarking
text       none empty high nomarking
footer     none empty high nomarking
before    command
inbetween command
after     command
alternative normal inmargin middle text
command   \command#1#2
numbercommand \command#1
textcommand \command#1
prefix    + - text
placehead yes no
incrementnumber yes no file
align     left right normal broad
tolerance verystrict strict tolerant verytolerant stretch
indentnext yes no
file      name
expansion yes command no
```

```
\setupheader[...][...,...=...,...]

...
      text margin edge
state     normal stop start empty high none nomarking name
strut    yes no
style      normal bold slanted boldslanted type cap small... command
leftstyle  normal bold slanted boldslanted type cap small... command
rightstyle normal bold slanted boldslanted type cap small... command
leftwidth  dimension
rightwidth dimension
before    command
after     command
```

\setupheadertexts[.1.][.2.][.3.]

- .1. text margin edge
- .2. text section date mark pagenumber
- .3. text section date mark pagenumber

\setupheadernumber[.1.][.2.]

- .1. section
- .2. number +number -number

\setupheads[...,...=...,...]

```
sectionnumber yes number no
alternative   normal margin middle text paragraph
separator    text
command     \command#1#2
```

```
\setupheadtext[...][...=...]
```

```
...      nl fr en uk de es cz ...
name    text
```

```
\setuphyphenmark[...=...]
```

```
sign   -- --- - ) (= /
```

```
\setupindentations[...,...,...][...,...=...,...]
```

```
...          name
style      normal bold slanted boldslanted type cap small... command
headstyle  normal bold slanted boldslanted type cap small... command
width      fit dimension
text       text
sample     text
before     command
after      command
distance   dimension
separator  text
```

```
\setupindenting[...,...,...]
```

```
...      none small medium big next first dimension
```

```
\setupinmargin[...][...,...=...,...]
```

```
...          left right number
location   left right both
style      normal bold slanted boldslanted type cap small... command
before     command
after      command
align      inner outer left right middle normal no yes
line       number
distance   dimension
separator  text
...=...      see \setupframed
```

```
\setupinteraction[...,...=...,...]
```

state	<u>start</u> <u>stop</u>
menu	<u>on</u> <u>off</u>
page	<u>yes</u> <u>no</u>
click	<u>yes</u> <u>no</u>
split	<u>yes</u> <u>no</u>
display	new
openaction	<i>reference</i>
closeaction	<i>reference</i>
openpageaction	<i>reference</i>
closepageaction	<i>reference</i>
calculate	<i>name</i>
strut	<u>yes</u> <u>no</u>
width	<i>dimension</i>
height	<i>dimension</i>
depth	<i>dimension</i>
style	normal <u>bold</u> slanted boldslanted type cap small... <i>command</i>
color	<i>name</i>
contrastcolor	<i>name</i>
symbolset	<i>name</i>
title	<i>text</i>
subtitle	<i>text</i>
author	<i>text</i>
date	<i>text</i>

```
\setupinteractionbar[...,...=...,...]
```

state	<u>start</u> <u>stop</u>
alternative	a <u>b</u> c d e f g
symbol	<u>yes</u> <u>no</u>
width	<i>dimension</i> hoogte fit
height	<i>dimension</i> hoogte fit
depth	<i>dimension</i>
color	<i>name</i>
step	<i>number</i> small medium big
...=...	see \setupframed

```
\setupinteractionmenu[...,...,...][...,...=...,...][..., {[ref,...]} , ...]
```

...	<i>left</i> <i>right</i> <i>top</i> <i>bottom</i> <i>name</i>
before	<i>command</i>
after	<i>command</i>
inbetween	<i>command</i>
left	<i>command</i>
right	<i>command</i>
middle	<i>command</i>
state	<u>start</u> <u>stop</u> none local
style	normal <u>bold</u> slanted boldslanted type cap small... <i>command</i>
color	<i>name</i>
distance	overlay <i>dimension</i>
samepage	yes empty no none
unknownreference	yes empty no none
leftoffset	<i>dimension</i>
rightoffset	<i>dimension</i>
topoffset	<i>dimension</i>
bottomoffset	<i>dimension</i>
position	<u>yes</u> <u>no</u>
...=...	see \setupframed

```
\setupinteractionscreen[...,...=...,...]
```

width *dimension* fit max
height *dimension* fit max
backspace *dimension*
topspace *dimension*
horoffset *dimension*
veroffset *dimension*
option max bookmark
delay *number* none

```
\setupinterlinespace[...]| [...,...=...,...]
```

... reset small medium big on off
height *number*
depth *number*
line *dimension*
top *number*
bottom *number*

```
\setupitemize[.1.][...,.2.,...][...,...=...,...]
```

.1. *number* each
.2. standard *n**broad *n**serried packed unpacked stopper joinedup atmargin inmargin autointro loose section
intext
margin no standard *dimension*
width *dimension*
distance *dimension*
factor *number*
items *number*
start *number*
before *command*
inbetween *command*
after *command*
left *text*
right *text*
beforehead *command*
afterhead *command*
headstyle normal bold slanted boldslanted type cap small... *command*
marstyle normal bold slanted boldslanted type cap small... *command*
symstyle normal bold slanted boldslanted type cap small... *command*
stopper *text*
n *number*
symbol *number*
align left right normal
indentnext yes no

```
\setupitems[...,...=...,...]
```

location left right inmargin top bottom
symbol 1 2 ... n a ... *text* none
width *dimension*
n *number* unknown
before *command*
inbetween *command*
align left right middle margin
after *command*

```
\setuplabeltext[...][...=...]
```

... nl fr en uk de es cz ..
name *text*

```
\setuplanguage[...][..., ...=..., ...]
```

... nl fr en uk de es cz ..
...=... see \installlanguage

```
\setuplayout[..., ...=..., ...]
```

width	<i>dimension</i>	fit middle
height	<i>dimension</i>	fit middle
backspace	<i>dimension</i>	
topspace	<i>dimension</i>	
margin	<i>dimension</i>	
leftmargin	<i>dimension</i>	
rightmargin	<i>dimension</i>	
header	<i>dimension</i>	
footer	<i>dimension</i>	
top	<i>dimension</i>	
bottom	<i>dimension</i>	
leftedge	<i>dimension</i>	
rightedge	<i>dimension</i>	
headerdistance	<i>dimension</i>	
footerdistance	<i>dimension</i>	
topdistance	<i>dimension</i>	
bottomdistance	<i>dimension</i>	
leftmargindistance	<i>dimension</i>	
rightmargindistance	<i>dimension</i>	
leftedgedistance	<i>dimension</i>	
rightedgedistance	<i>dimension</i>	
horoffset	<i>dimension</i>	
veroffset	<i>dimension</i>	
style	normal bold slanted boldslanted type cap small...	<i>command</i>
marking	on off	<i>color</i>
location	left middle right bottom top	<u>singlesided</u> doublesided
scale	<i>dimension</i>	
nx	<i>number</i>	
ny	<i>number</i>	
dx	<i>dimension</i>	
dy	<i>dimension</i>	
lines	<i>number</i>	
grid	yes no	
bottomspace	<i>number</i>	
cutspace	<i>number</i>	

```
\setuplegend[..., ...=..., ...]
```

n	<i>number</i>
distance	<i>dimension</i>
inbetween	<i>command</i>
width	<i>dimension</i>
height	<i>dimension</i>
location	right <u>bottom</u>
bodyfont	5pt ... 12pt small big

```
\setuplinenumbering[..., ...=..., ...]
```

conversion	<u>numbers</u> characters Characters romannumerals Romannumerals text	
start	<i>number</i>	
step	<i>number</i>	
width	<i>dimension</i>	
location	intext <u>inmargin</u>	
style	normal bold slanted boldslanted type cap small...	<i>command</i>
prefix	<i>text</i>	
referencing	on off	

```
\setuplines[...,...=...,...]
```

before	<i>command</i>
after	<i>command</i>
inbetween	<i>command</i>
indenting	yes <u>no</u> even odd

```
\setuplinewidth[...]
```

...	<i>dimension</i>
-----	------------------

```
\setuplist[...,...,...][...,...=...,...]
```

...	<i>name</i>
state	<u>start</u> stop
alternative	a <u>b</u> c ... none command
coupling	on <u>off</u>
criterium	<u>section</u> <u>local</u> previous current all
pageboundaries	<u>list</u>
style	normal bold slanted boldslanted type cap small... <i>command</i>
numberstyle	normal bold slanted boldslanted type cap small... <i>command</i>
textstyle	normal bold slanted boldslanted type cap small... <i>command</i>
pagestyle	normal bold slanted boldslanted type cap small... <i>command</i>
color	<i>name</i>
command	\command#1#2#3
numbercommand	\command#1
textcommand	\command#1
pagecommand	\command#1
interaction	<u>sectionnumber</u> text pagenumber all
before	<i>command</i>
after	<i>command</i>
inbetween	<i>command</i>
left	<i>text</i>
right	<i>text</i>
label	yes <u>no</u>
prefix	<u>yes</u> no
pagenumber	<u>yes</u> no
sectionnumber	yes no
aligntitle	yes <u>no</u>
margin	<i>dimension</i>
width	<i>dimension</i> fit
height	<i>dimension</i> fit broad
depth	<i>dimension</i> fit broad
distance	<i>dimension</i>
separator	<i>text</i>
symbol	none 1 2 3 ...
expansion	yes <u>no</u> command
maxwidth	<i>dimension</i>
...=...	see \framed

```
\setupmakeup[...][...,..=...,..]

...          name
width        dimension
height       dimension
voffset      dimension
hoffset      dimension
page         left yes right
commands     command
doublesided  yes no empty
headerstate  normal stop start empty none nomarking
footerstate  normal stop start empty none nomarking
textstate    normal stop start empty none nomarking
topstate     stop start
bottomstate  stop start
pagestate   stop start
color        name
```

```
\setupmarginblocks[...,..=...,..]

location    inmargin left middle right
style       normal bold slanted boldslanted type cap small... command
width       dimension
align       left middle right no
top         command
inbetween   command
bottom      command
left        command
right       command
before      command
after       command
```

```
\setupmarginrules[...=...]

level       number
thickness   dimension
```

```
\setupmarking[...][..=..]

...          name
state       start stop
separator   command
expansion   yes no
```

```
\setupnarrower[...,..=...,..]

left        dimension
right       dimension
middle     dimension
```

```
\setupnumbering[...,..=...,..]

way         bytext bysection bychapter
state      start stop
```

```
\setupoppositeplacing[...=..]

state      start stop
```

```
\setupoutput[...,...,...]
```

... *name*

```
\setuppagenumber[...,...=...,...]
```

number *number*
state start stop keep

```
\setuppagenumbering[...,...=...,...]
```

alternative singlesided doublesided
location header footer left right middle margin marginedge inleft inright
conversion numbers characters Characters romannumerals Romannumerals
style normal bold slanted boldslanted type cap small... *command*
left text
right text
way bytext bysection bypart
text text
numbersePARATOR text
textsePARATOR text
sectionnumber yes no
separator text
strut yes no
state start stop
command \command#1

```
\setuppagetransitions[...,...,...]
```

... *reset number*

```
\setuppallet[...]
```

... *name*

```
\setuppapersize[...,.1,...][...,.2,...]
```

- .1. A3 A4 A5 A6 letter ... CD *name* landscape mirrored rotated 90 180 270
- .2. A3 A4 A5 A6 letter ... *name* landscape mirrored rotated negative 90 180 270

```
\setupparagraphnumbering[...,...=...,...]
```

state start stop reset line
style normal bold slanted boldslanted type cap small... *command*
distance *dimension*

```
\setupparagraphs[.1.][.2.][...,..=...,...]  
.1.      name  
.2.      number each  
style     normal bold slanted boldslanted type cap small... command  
width    dimension  
height   dimension  
align    left right middle width breedte  
tolerance verystrict strict tolerant verytolerant stretch  
distance dimension  
before   command  
after    command  
inner   command  
command  command  
rule    on off
```

```
\setuppositioning[...,..=...,...]
```

```
state    start overlay  
unit    cm pt em mm ex es in  
factor   number  
scale   number  
offset  yes no  
xstep   absolute relative  
ystep   absolute relative
```

```
\setupprofiles[...,..=...,...]
```

```
option  test
```

```
\setupprograms[...,..=...,...]
```

```
directory  text
```

```
\setuppublications[...,..=...,...]
```

```
alternative  apa normal  
...=...       see \setupenumerations
```

```
\setupquote[...,..=...,...]
```

```
before   command  
after    command  
style    normal bold slanted boldslanted type cap small... command  
color   name  
location text margin
```

```
\setuppreferencelist[...,...,..][...,..=...,...]
```

```
...      name  
state   start stop  
criterium section local previous all  
command  command  
before   command  
after    command
```

```
\setupreferencing[...==...]
state      start stop
sectionnumber yes no
prefix      + - text
interaction   label text all symbol
width       dimension
left        command
right       command
convertfile yes no small big
separator    text
autofile     yes no page
global       yes no
```

```
\setupregister[.1.][.2.][...,...==...,...]
```

```
.1.
.2.          name
n            number
balance      yes no
align        yes no
style         normal bold slanted boldslanted type cap small... command
pagestyle     normal bold slanted boldslanted type cap small... command
textstyle     normal bold slanted boldslanted type cap small... command
indicator    yes no
coupling     yes no
sectionnumber yes no
criterium    section local all part
distance     dimension
symbol       1 2 ... n a ... none
interaction   pagenumber text
expansion    yes command no
referencing  on off
command      \command#1
location      left middle right
maxwidth     dimension
unknownreference empty none
```

```
\setuprotate[...,...==...,...]
```

```
rotation    number
...==...     see \setupframed
```

```
\setuprule[...][...,...==...,...]
```

```
...          name
depth      dimension
height     dimension
width      dimension
spacebefore dimension
spaceafter  dimension
color       name
```

```
\setscreens[...,...==...,...]
```

```
method      dot rule external
resolution  number
factor      number
screen      number
```

```
\setupsection[.1.][.2.][...,..=...,...]  
.1.      name  
.2.      name  
conversion   numbers characters Characters romannumerals Romannumerals  
previousnumber yes no
```

```
\setupsectionblock[...][...,..=...,...]  
...      name  
number  yes no  
page    yes right  
before   command  
after    command
```

```
\setsheets[...,..=...,...]  
alternative  number  
text        text  
size        small medium big  
style        normal bold slanted boldslanted type cap small... command  
number      number joinedup
```

```
\setupsorting[...][...,..=...,...]  
...      name  
before   command  
after    command  
command  \command#1  
state    start stop  
criterium all used  
style    normal bold slanted boldslanted type cap small... command  
expansion yes command no
```

```
\setupspacing[...]  
...      broad packed
```

```
\setupstickers[...,..=...,...]  
alternative  a  
n          number all  
location    margin left right middle
```

```
\setupstrut[...]  
...      yes no cap text
```

```
\setupsubpagenumber[...,..=...,...]  
way      bytext bysection bypart  
state   start stop none
```

```
\setupsymbolset[...]  
...      name
```

```
\setupynchronization[...,...=...,...]
```

state start stop

```
\setupynchronizationbar[...,...=...,...]
```

alternative page local
width *dimension* hoogte fit
height *dimension*
style normal bold slanted boldslanted type cap small... *command*
color *name*
...=... see \setupframed

```
\setupsynonyms[...][...,...=...,...]
```

... *name*
textstyle normal bold slanted boldslanted type cap small... *command*
synonymstyle normal bold slanted boldslanted type cap small... *command*
location left right top serried inmargin inleft inright
width *dimension*
state start stop
criterium all used
conversion yes no
expansion yes command no
command \command#1#2#3

```
\setupsystem[...,...=...,...]
```

resolution *number*
file *text*
directory *text*
random normal small medium big *number*

```
\setuptab[...,...=...,...]
```

sample *text*
width *dimension*
headstyle normal bold slanted boldslanted type cap small... *command*
location left right

```
\setuptables[...,...=...,...]
```

distance small medium big
bodyfont 5pt ... 12pt small big
HL *number* small medium big none
VL *number* small medium big none
depth *number* strut
height *number* strut
rulethickness *dimension*
rulecolor *name*
align right middle left normal
commands *command*
align left middle right normal
background screen color none
backgroundscreen *number*
backgroundcolor *name*

```
\setuptabulate[...][..., ...=..., ...]
```

... *name*
unit *dimension*
indenting yes no
before *command*
after *command*
inner *command*
EQ *text*
rulecolor *name*
align left middle right normal
rulethickness *dimension*
distance blank depth *dimension* small medium big none

```
\setuptext[...][..., ...=..., ...]
```

... see \setupheader
...=... see \setupheader

```
\setuptextposition[...][..., ...=..., ...]
```

... *name*
...=... see \setuppositioning

```
\setuptextrules[..., ...=..., ...]
```

location left inmargin
before *command*
after *command*
inbetween *command*
width *dimension*
distance *dimension*
bodyfont 5pt ... 12pt small big
color *name*
style normal bold slanted boldslanted type cap small... *command*
rulecolor *name*

```
\setuptexttexts[.1.][.2.][.3.]
```

.1. *text* margin edge
.2. *text* section date mark pagenumber
.3. *text* section date mark pagenumber

```
\setuptextvariable[...][..., ...=..., ...]
```

... *name*
left *text*
right *text*
distance *dimension*
command \command#1
strut yes no cap *text*

```
\setupthinrules[...=...]  
  
interlinespace small medium big  
n number  
before command  
inbetween command  
after command  
color name  
backgroundcolor name  
height dimension max  
depth dimension max  
alternative a b c d  
rulethickness dimension
```

```
\setuptolerance[...,...,...]  
  
... horizontal vertical stretch space verystrict strict tolerant verytolerant
```

```
\setuptop[...][...,...=...,...]  
  
... see \setupheader  
...=... see \setupheader
```

```
\setuptoptexts[.1.][.2.][.3.]  
  
.1. text margin edge  
.2. text section date mark pagenumber  
.3. text section date mark pagenumber
```

```
\setuptype[...=...]  
  
space on off  
option slanted normal none  
style normal bold slanted boldslanted type cap small... command  
color name
```

```
\setuptyping[...][...,...=...,...]  
  
... file typing name  
space on off  
page yes no  
option slanted normal commands color none  
text yes no  
icommand command  
vcommand command  
ccommand command  
before command  
after command  
margin dimension standard yes no  
evenmargin dimension  
oddmargin dimension  
blank dimension small medium big standard halffline line  
escape /  
indentnext yes no  
style normal bold slanted boldslanted type cap small... command  
color name  
palet name colorpretty  
lines yes no hyphenated
```

```
\setupunderbar[...,...=...,...]
```

alternative a b c
rulethickness *dimension*
bottomoffset *dimension*
topoffset *dimension*
rulecolor *name*

```
\setupurl[...,...=...,...]
```

style normal bold slanted boldslanted type cap small... *command*
urlalternative none both before after
urlspace yes no

```
\setupversions[...,...=...,...]
```

number *number*
style normal bold slanted boldslanted type cap small... *command*

```
\setupwhitespace[...]
```

... none small medium big line fixed fix *dimension*

```
\sheet[...]
```

... *text*

```
\showbodyfont[...,...,...]
```

... see \setupbodyfont

```
\showbodyfontenvironment[...,...,...]
```

... see \setupbodyfont

```
\showcolor[...]
```

... *name*

```
\showcolororgroup[.1.][...,2.,...]
```

.1. *name*
.2. horizontal vertical name value number

```
\showexternalfigures[...,...=...,...]
```

alternative a b c

```
\showfields[...,...,...]
```

... *name*

```
\showframe[...]
...
text margin edge
```

```
\showgrid
```

```
\showlayout
```

```
\showmakeup
```

```
\showpalet[.1.][...,2,...]
.1.    name
.2.    horizontal vertical name value
```

```
\showprint[...,.1.,...][...,2.,...][...,=,...]
...=..  see \setuppapersize
...=..  see \setuppapersize
...=..  see \setuplayout
```

```
\showsetups
```

```
\showstruts
```

```
\showsymbolset[...]
...
name
```

```
\somepline[ref]
```

```
\somewhere{.1.}{.2.}[ref]
.1.    text
```

```
\sort[.1.]{.2.}
.1.    text
.2.    text
```

```
\space
```

```
\splitfloat[...,...=,...]{.1.}{.2.}
...=..  see \setupfloatsplitting
```

```
\startalignment ... \stopalignment[...]
```

...=... see \setupalign

```
\startbackground ... \stopbackground
```

```
\startbuffer[...] ... \stopbuffer
```

... *name*

```
\startcolor[...] ... \stopcolor
```

... *name*
... *text*

```
\startcolumns[...,...=...,...] ... \stopcolumns
```

...=... see \setupcolumns

```
\startcombination[...] ... \stopcombination
```

... *n*m*

```
\startcomment[...][...,...=...,...] ... \stopcomment
```

... *name*
...=... see \setupcomment

```
\startcomponent ... ... \stopcomponent
```

... *file*

```
\startdescription{...} ... \stopdescription
```

... *text*

```
\startdocument[...] ... \stopdocument
```

... *name*

```
\startenumeration ... \stopenumeration
```

```
\startenvironment ... ... \stopenvironment
```

... *file*

```
\startfact\ geg.1.\.2.\.3.\\\geg ... \stopfact
```

.1. *text*
.2. *text*
.3. *text*

```
\startfigure[.1.][.2.][...,...=...,...] ... \stopfigure
```

.1. *name*
.2. *file*
factor *number*
frame *on off*

```
\startfloattext[.1.][ref]{.2.}{.3.} ... \stopfloat
```

.1. *left right high middle low offset tall*
.2. *text*
.3. *text*
.4. *text*

```
\startformula ... \stopformula
```

... *formula*

```
\startframedtext[...][...,...=...,...] ... \stopframedtext
```

... *left right middle none*
...=... see \setupframedtexts

```
\starthiding ... \stophiding
```

```
\startinteractionmenu[...] ... \stopinteractionmenu
```

... *name*

```
\startitemize[...,...,...][...,...=...,...] ... \stopitemize
```

... a A K A n N m r R K R *number* continue standard *n*broad n*serried packed stopper joinedup atmargin inmargin intro columns*
...=... see \setupitemize

```
\startlegend[.1.]\\leg.2.\.3.\.4.\\\leg ... \stoplegend
```

.1. *two*
.2. *text*
.3. *text*
.4. *text*

```
\startline[ref] ... \stopline
```

```
\startlinecorrection ... \stoplinecorrection
```

```
\startlinenumbering[...] ... \stoplinenumbering  
...     continue
```

```
\startlines ... \stoplines
```

```
\startlocal ... \stoplocal
```

```
\startlocalenvironment ... \stoplocalenvironment
```

```
\startlocalfootnotes ... \stoplocalfootnotes  
...=... see \setupfootnotes
```

```
\startmakeup[...][...,...=...,...] ... \stopmakeup  
...     name  
...=... see \setupmakeup
```

```
\startmarginblock ... \stopmarginblock
```

```
\startmarginrule[...] ... \stopmarginrule  
...     number
```

```
\startnamemakeup ... \stopname
```

```
\startnarrower[...,...,...] ... \stopnarrower  
...     n*left n*middle n*right
```

```
\startopposite ... \stopopposite
```

```
\startoverlay{.1.}{.2.} ... \stopoverlay  
.1.     text  
.2.     text
```

```
\startoverview[...,...,...] ... \stopoverview  
...     name
```

```
\startpacked[...] ... \stoppacked  
...     blank
```

```
\startparagraph ... \stopparagraph
```

```
\startpositioning ... \stoppositioning
```

```
\startpostponing ... \stoppostponing
```

```
\startproduct ... ... \stopproduct  
... file
```

```
\startprofile[...,...,...] ... \stopprofile  
... name
```

```
\startproject ... ... \stopproject  
... file
```

```
\startquotation[...,...,...] ... \stopquotation  
... n*left n*middle n*right
```

```
\startregister[.1.]{...+.2.+...}  
.1. text  
.2. text
```

```
\startsymbolset[...] ... \stopsymbolset  
... name
```

```
\startsynchronization ... \stopsynchronization
```

```
\starttable[...] ... \stoptable  
... text name
```

```
\starttables[...] ... \stoptables  
... text name
```

```
\starttabulate[...][...,...=...,...] ... \stoptabulate  
... text  
...=... see \useexternalfigure
```

```
\starttextrule[.1.]{.2.} ... \stoptextrule
```

.1. top bottom
.2. text

```
\starttyping ... \stotyping
```

```
\startunpacked ... \stopunpacked
```

```
\startversion[...,...,...] ... \stopversion
```

... *number*

```
\stretched{...}
```

... text

```
\sub[ref,...]
```

```
\subject[ref,...]{...}
```

... text

```
\subsection[ref,...]{...}
```

... text

```
\subsubsection[ref,...]{...}
```

... text

```
\subsubsubsection[ref,...]{...}
```

... text

```
\subsubsubsubsection[ref,...]{...}
```

... text

```
\switchtobodyfont[...,...,...]
```

... 5pt ... 12pt small big global

```
\switchtorawfont[...]
```

... *name*

```
\sym{...}
```

```
\symbol[.1.][.2.]
```

- .1. *name*
- .2. *name*

```
\synchronizationbar[...][..., .-=..., ...]
```

... *name*
alternative page local
.=-... see \setupynchronizationbar

```
\synchronize
```

```
\synonym[.1.]{.2.}{.3.}
```

- .1. *text*
- .2. *text*
- .3. *text*

```
\tab[.1.].2.\par
```

- .1. *text*
- .2. *text*

```
\tex{...}
```

- ... *text*

```
\textreference[ref]{...}
```

- ... *text*

```
\texrule[.1.]{.2.}
```

- .1. *top bottom*
- .2. *text*

```
\textvariable[...]
```

- ... *name*

```
\thinrule
```

```
\thinrules[.=-...]
```

- .=-... see \setupthinrules

```
\title[ref,...]{...}
```

... *text*

```
\tooltip[.1.]{.2.}{.3.}
```

.1. *left right middle*
.2. *text*

```
\translate[...,...=...,...]
```

name *text*

```
\typ{...}
```

... *text*

```
\type{...}
```

... *text*

```
\typebuffer[...]
```

... *name*

```
\typefile{.1.}{.2.}
```

.1. *name*
.2. *file*

```
\underline{...}
```

... *text*

```
\underbars{... ... ...}
```

... *text*

```
\useblocks[...,.1.,...][...,.2.,...]
```

.1. *name*
.2. *name*

```
\usecommands{...}
```

```
\usedirectory[...,...,...]
```

... *name reset*

```
\useencoding[...,...,...]
```

```
...     name
```

```
\useexternaldocument[.1.][.2.][.3.]
```

```
.1.     name  
.2.     file  
.3.     text
```

```
\useexternalfigure[.1.][.2.][...,..=...,...]
```

```
.1.     name  
.2.     file  
scale   number  
factor  max fit broad  
wfactor number max broad fit  
hfactor number max broad fit  
width   dimension  
height  dimension  
frame   on off  
preset  yes no  
display file  
preview yes no  
repeat  yes no  
object  yes no  
type    eps mps pdf tif png jpg mov tex  
method  eps mps pdf tif png jpg mov tex
```

```
\useexternalfile[.1.][.2.][.3.][...,..=...,...]
```

```
.1.     name  
.2.     name  
.3.     file  
bodyfont 5pt ... 12pt small big
```

```
\useexternalfiles[...][...,..=...,...]
```

```
...     name  
bodyfont 5pt ... 12pt small big  
file    file
```

```
\useexternalsoundtrack[.1.][.2.]
```

```
.1.     name  
.2.     file
```

```
\usemodule[...,...,...]
```

```
...     name
```

```
\usereferences[...,...,...]
```

```
...     file
```

```
\usespecials[...,...,...]
```

... *reset name*

```
\usesymbols[...]
```

... *name*

```
\useURL[.1.][.2.][.3.][.4.]
```

.1. *name*
.2. *text*
.3. *file*
.4. *text*

```
\version[...]
```

... final concept temporary

```
\v1[...]
```

... *number*

```
\WEEKDAY{...}
```

... *number*

```
\weekday{...}
```

... *number*

```
\whitespace
```

```
\WORD{...}
```

... *text*

```
\Word{...}
```

... *text*

```
\wordright{...}
```

... *text*

```
\Words{... ... ...}
```

... *text*

```
\WORDS{.. . . .}
```

```
... text
```

```
\writebetweenlist[.1.]{.2.}
```

```
.1. section name
```

```
\writetolist[.1.]{.2.}{.3.}
```

```
.1. section name
```

```
\writetoreferencelist[.1.]{.2.}{.3.}
```

```
.1. name
```

```
\writetoregister[.1.][.2.]{..+.3.+..}
```

```
.1.
```

```
.2. text
```

```
.3. text
```


PRAGMA ADE

Ridderstraat 27

8061GH Hasselt NL

www.pragma-ade.com